



# DATA SHEET

SLEEVES

## SLMFPE - MONOFILE

SLEEVING  
VIDAFLEX Monofile PE  
FLEXIGUARD



### Compositon / Properties:

Monofil PE is an expandable close weave sleeving, produced from braided PET-monofilaments. It is available in Black only. The Bore is expandable up to 300% and the particular advantage is the good retention of roundness. It offers a very good mechanical strength and also provide a very good resistance against salt water, oil, fuels and solvents. Operates at temperatures within the range of -70°C to 150°C.

### Application:


Used in motor vehicles for protection of hydraulic hoses, tubing and wiring harnesses. Especially used where cables are connected to moving parts and are constantly flexed.

### Pack Size:

Monofil PE is available on spools of 50, 100 and 250 metre, depending on diameter selected.

### DIMENSIONS

VIDAFLEX	SIZE CODE	BORE SIZE mm	Nom Wall Thickness mm	Weight Approx g/m
SLMFPE01.0BK	1.0	1.0 – 5.0	0.25	3.5
SLMFPE02.0BK	2.0	2.0 – 7.0	0.25	6
SLMFPE03.0BK	3.0	3.0 – 9.0	0.25	5
SLMFPE04.0BK	4.0	4.0 – 11.0	0.25	3.5
SLMFPE05.0BK	5.0	5.0 – 12.0	0.25	10
SLMFPE06.0BK	6.0	7.0 – 15.0	0.25	11.5
SLMFPE07.0BK	7.0	6.0 – 20.0	0.25	10.5
SLMFPE08.0BK	8.0	8.0 – 23.0	0.25	15
SLMFPE12.0BK	12.0	12.0 – 30.0	0.25	15.5
SLMFPE18.0BK	18.0	18.0 – 34.0	0.25	20.5
SLMFPE20.0BK	20.0	20.0 – 48.0	0.25	22.5
SLMFPE25.0BK	25.0	25.0 – 60.0	0.25	30



Temperature Index